




2SA733A
2SC945




2SA786FLN
2SC2021FLN




2SA755
2SC1419



2SB616
2SD586




2SD882




CD4011BCN
4011BPC
MC14011BCP
CD4011BE
CD4001BCN
4001BPC
CD4001BE
MC14001BCP

CD40106BCN
40106BPC
CD40106BE
CD4066BCN
4066BPC
CD4066BE
MC14066BCP



CD4022BCN
4022BPC
CD4022BE
MC14022BCP


CD4027BCN
4027BPC
CD4027BE
MC14027BCP





TA7136P




MSM5819




RC4558
RC4558P
TL431CP




QUARTS PLL DIRECT DR



DRIVE TURNTABLE



L-07D



SPECIFICATIONS

MOTOR & TURNTABLE

Drive System	Quartz PLL Direct-Drive
Motor	Coreless & Slotless DC Servo Motor (Starting Torque 2.5 kg.cm)
Turntable Platter	33 cm (13") Diameter, Aluminum Alloy Die-Cast Laminated with Duralumin.
	Weight: 5.5 kg (12.1 lbs) Including Non-Magnetized Stainless Turntable Sheet.
	Moment of Inertia: 1025 kg.cm ²
Speeds	2 Speeds, 33-1/3 and 45 rpm.
Wow & Flutter	Less than 0.020% (WRMS)
Rumble	DIN Weighted Better than -94 dB
Load Fluctuation	0% (within 120 g of tracking force)
Transient Load fluctuation	Less than 0.00015% (at 33-1/3 rpm, 400 Hz, 20 g.cm load)
	Less than 0.00008% (at 33-1/3 rpm, 1,000 Hz, 20 g.cm load)
Time & Temperature Drift	Limitation of Measurement

TONEARM

Type	Static-Balanced Type, J-Shaped Pipe Arm, EIA Plug in Connector.
Effective Tonearm Length	245 mm (9-5/8 inch)
Overhang	15 mm (9/16 inch)
Tracking Error	+2°28' - -1°11' - +1°48'
Stylus Pressure Variable Range	(150 mm) (85 mm) (50 mm)
	0 to 2 grams (50 mg Steps)
Usable Cartridge Weight	1 to 9 grams
(with Supplied Head-shell)	9 to 22 grams (with Addition of Included Weight)
Adjustable Height Range	Within 7 mm (1/4 inch)
Arm Base	By Helicord Fixture (0.1 mm Steps)
Head-shell	Collet Chuck Type, Weight: 1.5 kg (3.3 lbs)
	Compression-Molded Carbon and Boron Fibers.
	Weight: 12 g

ADDITIONAL FEATURES

Illuminated Quartz-Lock and Power Indicator
Electronic and Mechanically Controlled Brake
Arm-Height Adjuster
Anti-Skating Device
Oil-Damped Cueing Control
LED Speed Indicators
Adjustable Height Insulator (12 mm or 15/32")
with Level Indicator
Stylus Pressure Direct Readout Counter
Sub-Tonearm Space for 14-Inches Tonearm

MISCELLANEOUS

Power Requirement	AC 120 V, 60 Hz: U.S.A. & Canada Models
	AC 120/220-240 V (switchable), 50/60 Hz: Others
Power Consumption	11.0 Watts.....U.S.A. & Canada Models
	45.0 Watts.....Others
Dimensions	
Turntable and Motor	W 555 mm (21-7/8")
	H 160 mm (6-5/16")
	D 470 mm (18-1/2")
Control Unit	W 130 mm (5-1/8")
	H 110 mm (4-11/32")
	D 356 mm (14")
Weights	
Turntable and Motor	31.0 kg (68.2 lbs)
Control Unit	4.3 kg (9.5 lbs)

SUPPLIED ACCESSORIES

Low resistance & low capacitance phono cables with gold plated terminals, 45 rpm adaptor with overhang gauge, Turntable platter cover
Dust cloth, Screwdriver, Silicon cloth, Absorbers, Ground wire.

CABINET

The construction of this cabinet is made of an anti-resonance compression base (ARCB) with die-cast aluminum frame and mahogany composite material.

Kenwood follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.

Kenwood follows a policy of continuous advancements in development. For this reason specifications may be changed without notice.

Kenwood strebt ständige Verbesserungen in der Entwicklung an. Daher bleiben Änderungen der technischen Daten jederzeit vorbehalten.

Kenwood poursuit une politique de progrès constants en ce qui concerne le développement. Pour cette raison, les spécifications sont sujettes à modifications sans préavis.

